

Heather Platform

The Heather installation is designed to accept production fluids from Heather field and Broom field via subsea tieback. The production fluids are processed and separated into oil, gas and water. The processed oil is exported to the Sullom Voe Terminal via Ninian Central platform, while the gas is routed through compression trains for lift gas purpose. Produced water is separated, treated and discharged overboard and sea-water is injected into both Broom and Heather fields to optimise production. Import gas is provided via the Western Leg gas pipeline to meet the fuel gas deficiencies on the platform.

Infrastructure Information

Description:	Sweet Crude Oil
Entry Specification:	Oil- Ninian Pipeline Entry Specification
Exit Specification:	Gas- No Gas export
Outline details of Primary separation processing facilities:	Oil passes through a single train, two stage separation process. Produced water is treated via hydrocyclones and compact flotation unit (CFU). This water is then discharged overboard.
Outline details of gas treatment facilities:	Gas flows via two out of three trains in a three stage compression process. All gas passes through a TEG dehydration package and is then used for gas lift and fuel gas purposes.

High Level Capacity Information

The basic capacity information is portrayed by colour coded 'traffic lights' that reflect thresholds of availability over the next 5 years

>25% capacity available	
5-25% capacity available	
<5% capacity available	

Processing Facility	Total Capacity	2019	2020	2021	2022	2023	Comments
Gas compression capacity	60* mmscf/day						*Designed for 60mmscf/day gas with all 3 compression trains online, however constraints on dehydration system limit this to 54mmscf/day
Gas export capacity	0* mmscf/day						*Existing gas import route is an old export facility, with the capacity of 26mmscfd.
Gas lift capacity	54 mmscf/day						
Produced water handling capacity	50000* bbls/day						*CFUs restricted to 50,000 bbls/day by upstream restriction orifice
Dehydration capacity	54 mmscf/day						
H2S removal capacity	0 mmscf/day						H2S is currently treated using H2S scavenger chemical injection. H2S Scavenger currently can remove 10-15mg/l in crude and up to 900ppm in gas phase.
Water injection capacity	70000 bbls/day						
Crude oil capacity	30000* bbls/day						*Crude oil capacity set on 1002 Export Pumps in operation

Contact Information

For further enquiries, please contact Donna Cameron on Tel +44(0)1224 975000 or email Donna.Cameron@enquest.com.

Disclaimer

All the above information is provided by EnQuest PLC (for itself, and other EnQuest group companies);

- In good faith and without any liability
- Without warranty, implied or express to its accuracy or relevance of use to any other party
- That in any agreement or arrangement with EnQuest PLC its use shall be “Subject to Contract”
- EnQuest PLC reserves the right to update and change the data at any time

Updated

March 2019